

Authority herein given and granted for a period of five (5) years from and after Date of Passage.

(Page 4 of 5)

Bigbelly® High Capacity Compactor

Configurations Mixed waste or single stream recycling (with appropriate markings)

Materials

RoHS compliant

Galvanized sheet metal steel interior and exterior construction

Heavy duty plastic side panels for dent and scratch resistance (recycled content)

Interior Bin Single bin is leak proof made out of low density polyethylene plastic

Power & Electronics

Polycrystalhne silicon cell PV module (20 watts) (30 watts HE [high energy] upgrade available)

PV panel protected by polycarbonate bubble Spill-proof sealed maintenance-free battery Self powered unit requires no wiring

Technical Specifications

Overall Machine Dimensions

Height 49 8" (1264mm) Width 25 (635mm) Depth 26 8" (681 mm)

Handle Height (ADA Compliant) 43 1" (1095mm)

Weight 270 lbs (122 kg), Shipping weight 300 lbs (136 08kg)

Hopper Opening 6" x 17" (152mm x 432mm)

Bin Volume 33 gallons (125 L) compacted trash approximately 150 gallons (568 L) uncompacted trash

Compactor Features

Compaction Up to 5-to-1 compaction ratio

Fully automated, microprocessor controlled system senses fullness and machine status

3 color LED status lamps indicate compacted trash level machine status and error codes

GPRS wireless data link for remote monitoring and management GPS assisted location service

Safety Features

CE approved

Fully interlocked access doors protect users and service personnel Locked front trash removal door (Locked rear door option available) Separately keyed service access

Fault-tolerant design for hopper insertion door prevents access to compaction area

Durability

Weather resistant, UV stabilized polyester powder-coat finish on all exterior parts

Electronic components temperature range of -40°F to +185°F

(-40°C to +85°C)

Fully weatherized, but in the event of a flood, Bigbelly can withstand ■ Up to 20" (508mm) of water without harming the electronics ■ Up to 36" (915mm) of water with only minor damage to electronics

Bigbelly Solar, Inc 150|A Street-Suite 103 Neqtfham, MA 02494 USA
Sales@Bigbelly ifeU Bigbelly co|nij'



Toll-free International FAX

+1 888 820 0300 +1 781 444 6002 +1 781 444 5651

lrfio_T«ehSpecs(BB5)_2015.Ji