

# Office of the City Clerk

City Hall 121 N. LaSalle St. Room 107 Chicago, IL 60602 www.chicityclerk.com

## **Legislation Text**

File #: O2014-9946, <b>Version</b> : 1				
ORDINANCE S Acct.	LEEPY'S No.	381413-24	Permit	No.
1115123	INO.	JU 14 13-24	ı Gillill	NO.

Be It Ordained by the City Council of the City of Chicago:

SECTION 1. Permission and authority are hereby given and granted to SLEEPY'S, upon the terms and subject to the conditions of this ordinance to maintain and use two (2) sign(s) projecting over the public right-of -way attached to its premises known as 2731 N. Clark St..

Said sign structure(s) measures as follows; along N. Clark:

One (1) at eighteen point eight three (18.83) feet in length, two (2) feet in height and twelve (12) feet above grade level.

One (1) at ten point five (10.5) feet in length, two (2) feet in height and twelve (12) feet above grade level.

The location of said privilege shall be as shown on prints kept on file with the Department of Business Affairs and Consumer Protection and the Office of the City Clerk.

Said privilege shall be constructed in accordance with plans and specifications approved by the Department of Transportation (Division of Project Development) and Zoning Department - Signs.

This grant of privilege in the public way shall be subject to the provisions of Section 10-28-015 and all other required provisions of the Municipal Code of Chicago.

The grantee shall pay to the City of Chicago as compensation for the privilege #1115123 herein granted the sum of four hundred (\$400.00) per annum in advance.

A 25% penalty will be added for payments received after due date.

The permit holder agrees to hold the City of Chicago harmless for any damage, relocation or replacement costs associated with damage, relocation or removal of private property caused by the City performing work in the public way.

Authority herein given and granted for a period of five (5) years from and after Date of Passage.

Alderman

Michele Smith 43ra Ward

#### File #: O2014-9946, Version: 1

### Page 1

(Page 3 of 3)

SIGN A | 24" Starf! / 24- TOP

T> IK' Channel Lbi cn a racowvy / C Internally IHunmatod LED

Top of ton to grade = 14-2 1\h of ugn to grade o1Z\*-Z 1/4\*

Sign Layout Detail

Scale 1/4"=r-0"

1IW [1261

#### The Mattress Professionals

5i>ecificntions:. LED Ch.innel L'ctlcfs / "Star

- Sizection Floated Metal
  0 040" Ahim-num letter returns punted to match BUck
  1 Jewekte Innicap (Black) bonded to face "8 pan head screws to returns
  3 mm Sgnabond Lite composite backs fastered to raturna W 1/2" 16 gauga staples Seal wr VOC compliant 360 white latax cautk to prevent moaxure penetration (Interior of ifgn can painted uttra white for max Summation)
  Letters- Sloan Valus Lna Plus Short Red LED modules SHX: Sloan Vacua Lmo Plui Short Vrhrto LED"
  LUBO- 3/18" 2415 Rad LO Ja crylic
  Slar- 3/16" 2447 White LD acrylic wi vinyl 3M 3630-125 Golden YeBow vtnyl wth 3M 7125-22 Matte BUck wnyi outtmo
  UL Outdoor rated toggle type drisoormed switch of neoprene boot per NEC 600-6
  Primary electrical feed « UL condux / oatomer suppkad UL function box. Located al MI and of raoaway (top)

- 10 O OKTReceway (5.1/2" tallx 3 Wdeep fabricated aknwumj Painted to match facade
  11 ° "x 2" x 01675 Aluminum mounting tabs welded to raceway Mm mum 6" from each end and every 48" o c
  12 #12 x 1" TEC ecrawe with 11/4" fender washers
  13 Mounting flardware to so a

- 1 Exttng Facade Urtal

- 1 Exting Facade Urtal
  2 5\* Deep extruded afurmw ijo/i c\* parted black
  3 Signcomp\*2056 1 1/2\*hmge sl)to retainw painted black
  4 3/16\* While SO 404 Laxan w/ appbed 3M 3030-22 Slack vaiyloopy
  5 LET\* & Transformer- Sloan Valuo L-no Pxjs Short Whrte LEO\*
  6 UL Outdoor rated toggle type disconnect switch w/ naoprane boot par NEC 600-6
  7 Primary litelencal feed w UL condurt/ customer suppeed UL|unotion box
  8 Mountmg haidwaie to curt

Nola Electrical pesytring to be in the kmarporuon of each tetter (and -Star\*)

Red and White Sloan value Line Plus (4) 60w Transformers © 0 85 Total Amp\* 340 (1)20 amp 120V OrcutRaq

The ergn is to be rotated m accordance with the rexiurrements of AAcle 600 of fhe NabonaJ ElectricalCodo

1) Grounded and bonded per NEC 600 7/NEC 250
2) Extsfing branch orouil th compfeanee with NEC 600 5. not to exceed 20 amp)
3) SignistobeULfcstedperNEC600 3
4) UL dincortnot swdch per NEC 600 6- roquffod per ergn cornponant before leaving manufacturer\*

"For muffple sxjmv a disconnect is perrretted but not required for each sacbon
Section 63> LED Channel Letter

Raceway Scab nts

Section @ S/F Wall Sign LED'S Seals NTS

Address 2731 North Clark Street Cracaoo. IL 60814