

Office of the City Clerk

City Hall 121 N. LaSalle St. Room 107 Chicago, IL 60602 www.chicityclerk.com

Legislation Text

File #: Or2018-327, Version: 1

CITY COUNCIL COMMITTEE ON ZONING, LANDMARKS AND BUILDING STANDARDS

COUNCIL ORDER

RE: Approval of sign over 100 square feet in area or over 24 feet above grade

ORDERED, that the City Council hereby approves the following sign application submitted by:

ApDicant«: Western; Bell, Inc. - dba: Taco Bell

(* The Applicant is the owner of the real property or the business tenant of the real property. Do not list the sign contractor, sign erector, sign company or advertising entity in the above space.)

This Order approves the following sign in accordance with Municipal Code of Chicago Section 13-20-680:

Address of Sign: 241 0 S. WeStem Ave.

Chicago, IL606_

B3-1 i

Zoning District:

DOB Sign Permit Application #: 1 UU JO 1 AU

Sign Details: v

On-premise OR Off-premise

Х

Static sign OR Dynamic-image display sign

2

3. Number of sign faces

4. Projecting over the public way (Yes or No) If yes, Public Way Use

fi 11 11 7

5. Dimensions: Length feet inches Height feet inches

total square feet in area: feet ^ inches

6. Height above grade: feet ^ inches

7. Elevation (side of building or lot where the sign will be erected): Northeast

8. Name of Sign Contractor/Erector: Identity Services, LLC

To be legal, such sign shall comply with ail provisions of Title 17 of the Chicago Municipal Code ("Zoning Ordinance") and all other provisions of the Municipal Code governing the permitting, construction and maintenance and removal of signs and sign structures. Failure of the applicant and the applicant's successors to comply shall be grounds for invalidation or revocation of the sign permit.

Zfbht 25

Alderman

Pylon Sign - Breakfast - 75sf

10" [254mm]

SPECIFICATIONS

DESIGN PARAMETERS

Structural adequacy shall be the manufacturer's responsibility using the following criteria:

90 MPH 3 second gust wind speed per ASCE 7-05 (115 MPH - ASCE 7-10). Category II, Exposure C. 150 PSF per foot of depth allowable lateral soil bearing pressure.

- Compliant with national building codes and standards (IBC 2009, IBC 2015, AISC 14th Edition, ASCE 7-05, ASCE 7-10, ACI & Aluminum Design Manual)
- Refer to written documentation for material specifications.

Cabinet

- Extruded aluminum frame, 10" [254mm] deep with 2" [51mm] retainer
- Aluminum painted fillers
- .167 [5mm] pan-formed SG polycarbonate face with debossed reinforcement at main ID face 2nd surface digitally printed decal backed up with white
- .150 [4mm] pan-formed SG polycarbonate face at breakfast face
- Faces pinned into the retainer with mechanical fasteners as required
- Hingeable access for service

-SEE MATCH PLATE DETAIL

- 8"x8"x3/8" [203x203x10mm] STEEL TUBE

ELECTRICAL/ PERFORMANCE SPECIFICATIONS

- UL & NEC approval required. 12V, Class II UL approved system.
- If alternate LED's are used.
 - 50,000 hour system where no greater than 30% lumen depreciation is experienced at 50K hours.
 - Thermally managed surface mount devices (SMD).

LED(s): (324) AgiLight LS-PRO260-50K-2G3 White (5000K) LEDs (162 ft) or equivalent - pre-approval required mounted to both sides of 1"x1" [25mm x 25mm] alum, tube

Power Supply: (8) 12V/60W LED Power Supplies @ 0.9 amps ea. Total Load: 7.2 amps

Circuits(s): (1) 20 amp-120V

ELECTRICAL CONDUIT

3'-0" [914mm] DIA.

2.36 CU.YDS. CONCRETE REQ'D TACO BELL -1 GLEN BELL WAY, IRVINE, CA 92618 - 949.863.4500

LED LAYOUT CABINET

NOT FOR CONSTRUCTION AUGUST 2017 1" [25mm] THK. A36 PLATE

(4) 3 1/2"x3 1/Z X1/2" [89x89x13mm] STEEL GUSSET HSS 5 563 O.D. x .280 (42ksi)[141 O.D. x 7mm] 2" [51mm]-ELECTRICAL ACCESS HOLE MATCH PLATE DETAIL

8x8"x3/8" [203x203x10mm] STEEL TUBE 1 1/8" [29mm] DIA. HOLE (4 PLACES) FOR 1" [25mm] DIA. A325 BOLT

PARTICULAR CARE SHALL BE TAKEN TO PROVIDE SUFFICIENT PREHEAT OF THE THICKER ELEMENT FOR THE SOUNDNESS OF THE WELO. OTHERWISE, USE 5116" (emm) MIN. WELD PANTONE

PMS 2603C PMS 2577C Pantone Black Pantone White

File #: Or2018-327, Version: 1

GRAPHIC & COLOR SPECIFICATIONS:

PAINT

COLOR O Dark Purple © Light Purple O Black © White

3M 3630-20 SW2123

@ TB Bronze Tiger Drylac 49-66230 C33